



ITEMS	VALUES	UNIT
OPERATING WEIGHT	14.48	ton
BUCKET CAPACITY (SAE)	0.51	m ³
ENGINE RATED POWER	100/1,850	ps/rpm
ENGINE MAX. TORQUE	45.8/1,400	kg/rpm
SYSTEM PRESSURE (WORK/TRAVEL)	330(350)/3	kg/cm ²
SWING SPEED	10.8	rpm
TRAVEL SPEED (High/Low)	5.0/3.0	km/h
GRADEABILITY	70 (35°)	%(deg)
SHOE WIDTH	600	mm
GROUND PRESSURE	0.43	kg/cm ²
DIGGING FORCE BUCKET (Nor./Press. Up)	10.5/11.1	ton
DIGGING FORCE[ISO] ARM (Nor./Press. Up)	5.7/6.0	ton
Max. Digging reach (Std.)	8,295	mm
WORKING RANGE MAX. DIGGING DEPTH	5,500	mm
WORKING RANGE MAX. DIGGING HEIGHT	9,280	mm
WORKING RANGE REAR SWING RADIUS	14,080	mm
WORKING RANGE MIN. SWING RADIUS	9,280	mm
TRANSPOR - TATION DIMENSION OVERALL LENGTH	7,230	mm
TRANSPOR - TATION DIMENSION OVERALL WIDTH (STD.)	2,590	mm
TRANSPOR - TATION DIMENSION OVERALL HEIGHT	2,795	mm
TRANSPOR - TATION DIMENSION GROUND CLEARANCE	410	mm
TRANSPOR - TATION DIMENSION TRACK LENGTH	3,755	mm
TRANSPOR - TATION DIMENSION TRACK GAUGE(STD.)	1,990	mm

DX140LCR : STD BOOM (4,680 mm) STD ARM (2,500 mm) STD BUCKET (0.51m³)



35a Bonnyside Road, Bonnybridge FK4 2AD

T: 01324 815 055

M: 07793 184 825

E: info@mcinallyplant.com

www.mcinallyplant.com